



C-35 concrete @ 28 days with 10mm & 14mm aggregate used in the manufacture of this unit.

Steel reinforcing consists of 3No. R12mm bars with 20mm cover (minimum) & 30mm at ends. Rebar located by patent plastic spacers in unit.

- DO NOT SCALE USE FIGURED DIMENSIONS ONLY.
- ALL DIMENSIONS TO BE CHECKED ON SITE.
- A.P.C TO BE INFORMED OF ANY DISCREPANCIES BEFORE WORK PROCEEDS.

© COPYRIGHT: Ardee Precast Concrete.  
This drawing or any part thereof may not be copied or otherwise reproduced without the written permission of Ardee Precast Concrete.

Project:  
**TECHNICAL DATA SHEET.**

Title:  
**FLUE FIRE HEAD.**

Drawing No:  
**APC - 801**

Revision:

Date:  
**07-10-2011**

Sheet Size:  
**A4**

Drawing Scale:  
**1:10,**

Drawn By:  
**N.D.**

Checked By:



**Ardee Precast Concrete Ltd.**

Townparks Ardee Co. Louth  
Tel. +353(0)41 6856372  
Fax. +353(0)41 6857216

Email us at [info@ardeeprecastconcrete.com](mailto:info@ardeeprecastconcrete.com)  
Visit us at [www.ardeeprecastconcrete.com](http://www.ardeeprecastconcrete.com)